

PROFESSIONALLY ENGINEERED TO INSPECT 1 1/2" TO 10" DIAMETER PIPELINES



CAM

PIPELINE INSPECTION SYSTEMS

QUICKLY INSPECT & LOCATE

A WIDE VARIETY OF

PIPELINE PROBLEMS

**ace
2SL**



**ace
wifi**

**pro
2**



ace



**ace
100
micro**



Electric Eel®

DRAIN CLEANING TOOLS FOR PROFESSIONALS



CAM

PIPELINE INSPECTION SYSTEMS



CAM pro2

Features

- Rugged stainless steel housed 1.68" diameter self-leveling color camera
- 12.1" Daylight readable display
- 8" wheels for easy transport and maneuverability

Camera

- Rugged stainless steel housed 1.68" dia. self-leveling color camera with sapphire lens, 20 LED light ring and high resolution CCD element
- Flexible camera spring designed to navigate 3" P-traps
- Auto iris adjusts lighting automatically
- Impact-resistant polycarbonate light ring cover
- Industry standard 512HZ sonde



Reel & Frame

- Standard with 200 ft. of braided Fiberglass Premium 1/2" dia. push rod (reel capacity available up to 400 ft.)
- Secure-locking reel brake
- Rugged powder-coated steel tube and bar construction
- 8" wheels for easy transport and maneuverability

Monitor

- Audio/Video out jacks
- 12.1" Daylight readable display
- Record directly to USB flash drive
- Click touch controls and one touch recording
- 16 Pages of text writing with memory saves
- On screen footage counter
- Adjustable light controls
- Voice over recording (built-in)
- Rename files on flash drive after recorded
- 512 Hz sonde
- 2 Hour battery with built-in charger
- 8X Zoom function

((Wi Fi Option Available))



CAM ace2SL

Features

- Self-Leveling Color Camera
- One-Touch USB recording
- On-screen footage counter
- 8" wheels for easy transport and maneuverability



Ace 2 SL Monitor & USB



CAM acewifi

Features

- Wi Fi enables users to record video with their mobile device
- Custom downloaded APP enables the user to see the video and take snap shots



Wi Fi Antenna



CAM ace

Features

- Rugged stainless steel housed 1.68" dia. color camera with sapphire lens
- 200 ft. of braided Fiberglass Premium 1/2" dia. push rod



Screen Cover



Standard Features and Specifications for eCAM ACE 2 SL, eCAM ACE Wi Fi & eCAM ACE Pipeline Inspection Systems Include:

Camera > Self-Leveling Color Camera Standard on Ace 2 SL and Optional on Ace & Ace Wifi

- Rugged stainless steel housed 1.68" dia. color camera with sapphire lens, 20 LED light ring and high resolution CCD element
- Flexible camera spring designed to navigate 3" P-traps
- Auto iris adjusts lighting automatically
- Industry standard 512HZ sonde
- Impact-resistant polycarbonate light ring cover
- Camera options: .875" dia. color camera for inspecting 1 1/2" - 3" lines; 1.23" dia. color camera for inspecting 2" - 4" lines.

Monitor

- 5.4" LCD monitor with AR film for optimal viewing in sunlight encased in an anodized aluminum housing mounted to the reel
- Protective acrylic, anti-glare monitor shield
- Video output jack for recording option

Reel & Frame

- Rugged and portable powder-coated steel frame
- Standard with 200 ft. of braided Fiberglass Premium 1/2" dia. push rod
- Secure-locking reel brake
- Heavy-duty screen cover closes to protect the monitor when in transit or storage, flips up as a sun shield and can be retrofitted to existing units.



Optional Portable Battery Pack for ALL Ace Units



CAM ace100-micro

Features

((Wi Fi))

- Video is streamed directly to any mobile device which can be used as your monitor
- Easy to Use Wi Fi App
- Compact and portable
- Save files on your device; transfer via Email, Text, Cloud



Single Button Wi Fi Hub

- Inspects 1 1/2" - 3" dia. pipes up to 100 ft.
- Weighs only 15 lbs.
- 512HZ sonde
- 1" dia. camera head
- 100 ft. of .271" dia. push rod
- Resettable footage counter displays feet and meters



Mobile device not included

For More Information, Call 800-833-1212 or Visit Our Web Site at www.electriceel.com

Electric Eel®

DRAIN CLEANING TOOLS FOR PROFESSIONALS

Note: Always refer to operator's manual and safety instructions before operating any pipeline inspection equipment.

ELECTRIC EEL MANUFACTURING CO., INC.
501 W. Leffel Lane, Springfield, Ohio 45506
937-323-4644 Toll-Free: 800-833-1212 FAX: 937-323-3767
E-mail: info@electriceel.com www.electriceel.com 8/19 LT-17